



A black and white line drawing of a two-story row house. The house features a brick roof and horizontal siding. It has three windows on the second floor and three on the first floor. The central entrance is highlighted by a small porch with a brick pediment. The house is surrounded by landscaping, including tall trees on the left, a large bush on the right, and a row of tall grasses in front.

CV



- WALL ASSEMBLY - THE 1 OR 2HR FIRE RATED GYPSUM WALLBOARD/STUD WALL ASSEMBLY SHALL BE CONSTRUCTED OF THE MATERIALS & IN THE MANNER DESCRIBED IN THE INDIVIDUAL U300 OR U400 SERIES WALL OR PARTITION DESIGNS IN THE UL FIRE RESISTANCE DIRECTORY & SHALL INCLUDE THE FOLLOWING CONSTRUCTION FEATURES:
- A. STUDS - WALL FRAMING MAY CONSIST OF EITHER WOOD STUDS OR STEEL CHANNEL STUDS. WOOD STUDS TO CONSIST OF NOM. 2"x4" LUMBER SPACED 16" O.C. WITH NOM. 2"x4" LUMBER END PLATES AND CROSS BRACES. STEEL STUDS TO BE MIN. 3 1/2" WIDE BY 1-3/8" DEEP CHANNELS SPACED MAX. 24" O.C.
 - B. WALLBOARD GYPSUM - NOM. 5/8" THICK, 4' WIDE WITH SQUARE OR TAPERED EDGES. THE GYPSUM WALLBOARD TYPE, THICKNESS, NUMBER OF LAYERS, FASTENER TYPE AND SHEET ORIENTATION SHALL BE AS SPECIFIED IN THE INDIVIDUAL U300 OR U400 SERIES DESIGN IN THE UL FIRE RESISTANCE DIRECTORY. MAX. DIAM. OF OPENING IS 15'.
- THE HOURLY F RATING OF THE FIRESTOP SYSTEM IS 1HR WHEN INSTALLED IN A 1 HR FIRE RATED WALL AND IS 2 HR WHEN INSTALLED IN 2 HR FIRE RATED WALL.
2. THE FOLLOWING PENETRAIL - ONE METALLIC PIPE, CONDUIT OR TUBING TO BE INSTALLED EITHER CONCENTRICALLY OR ECCENTRICALLY WITHIN THE FIRESTOP SYSTEM. THE SPACE BETWEEN PIPES, CONDUITS OR TUBING AND THE STEEL SLEEVE (ITEM 3A) SHALL BE MIN. OF 0" (POINT CONTACT) TO MAX. 2-3/8". PIPE, CONDUIT OR TUBING TO BE RIGIDLY SUPPORTED ON BOTH SIDES OF WALL ASSEMBLY. THE FOLLOWING TYPES AND SIZES OF METALLIC PIPES, CONDUITS OR TUBING MAY BE USED:
 - A. STEEL PIPE - NOM. 12"Ø (OR SMALLER) SCHEDULE 10 (OR HEAVIER) STEEL PIPE.
 - B. IRON PIPE - NOM. 12"Ø (OR SMALLER) SERVICE WEIGHT (OR HEAVIER) CAST IRON SOIL PIPE, NOM. 12"Ø (OR SMALLER) OR CLASS 50 (OR HEAVIER) DUCTILE IRON PRESSURE PIPE.
 - C. CONDUIT - NOM. 6"Ø (OR SMALLER) STEEL CONDUIT OR NOM. 4"Ø (OR SMALLER) STEEL ELECTRICAL METALLIC TUBING.
 - D. COPPER TUBING - NOM. 6"Ø (OR SMALLER) TYPE L (OR HEAVIER) COPPER TUBING.
 - E. COPPER PIPE - NOM. 6"Ø (OR SMALLER) REGULAR (OR HEAVIER) COPPER PIPE.
 3. FIRESTOP SYSTEM - INSTALLED SYMMETRICALLY ON BOTH SIDES OF WALL ASSEMBLY. THE DETAILS OF THE FIRESTOP SYSTEM SHALL BE AS FOLLOWS:
 - A. STEEL SLEEVE - CYLINDRICAL SLEEVE FABRICATED FROM MIN. 0.019" THICK (NO. 28 GAUGE) GALV. SHEET STEEL AND HAVING A MIN. 2" LAP ALONG THE LONGITUDINAL SEAM. LENGTH OF STEEL SLEEVE TO BE EQUAL TO THICKNESS OF WALL PLUS 1" TO 4" SUCH THAT, WHEN INSTALLED, THE ENDS OF THE SLEEVE WILL PROJECT APPROXIMATELY 1/2" TO 2" BEYOND THE SURFACE OF THE WALL ON BOTH SIDES OF THE WALL ASSEMBLY. THE DIAM. OF THE OPENINGS CUT IN THE GYPSUM WALLBOARD LAYERS ON EACH SIDE OF THE WALL ASSEMBLY (CONCENTRIC WITH PIPE) TO BE 1" TO 2-1/2" LARGER THAN OUTSIDE DIAM. OF PIPE SUCH THAT, WHEN THE STEEL SLEEVE IS INSTALLED, AN ANNULAR SPACE OF MIN. 0" (POINT CONTACT) TO MAX. 2-3/8" WILL BE PRESENT BETWEEN THE STEEL SLEEVE AND THE PIPE AROUND THE ENTIRE CIRCUMFERENCE OF THE PIPE. SLEEVE INSTALLED BY COILING THE SHEET STEEL TO A DIAM. SMALLER THAN THE THROUGH OPENING, INSERTING THE COIL THROUGH THE OPENINGS AND RELEASING THE COIL TO LET IT UNCOIL AGAINST THE

NOM. PIPE DIAM IN.	WALL ASSEMBLY RATING HR.	CLOSED (C) OR VENTED (V)	T-RATING HR.
1/2 TO 3	1	C	1
1/2 TO 1-1/4	1	V	1
1/2 TO 1-1/4	2	C	2
1/2 TO 1-1/4	2	V	1
2	1	V	0

- MINNESOTA MINING & MFG. CO. - CP-25WB+
*BEARING THE UL CLASSIFICATION MARKING.

1. WOOD STUDS - NOMINAL 2"x4" @ 16" O.C., EFFECTIVELY CROSS BRACED AT MID-HEIGHT & FIRE STOPPED AT TOP & BOTTOM.
2. WALLBOARD GYPSUM+ - 5/8" THICK, 4' WIDE, APPLIED VERTICALLY. WALLBOARD ATTACHED TO STUDS & BEARING PLATES WITH 1 3/4" LONG GALV. NAILS WITH 1/2" Ø 28 DIAMETER SHANK @ 7" O.C. HEAD, SPACED 8" O.C.
G-P GYPSUM CORP. - TYPE DGG (FINISH RATING 20 MIN.)
3. WALLBOARD GYPSUM+ - 5/8" THICK, 4' WIDE, APPLIED VERTICALLY. WALLBOARD ATTACHED TO STUDS & BEARING PLATES WITH 1 3/4" LONG GALV. NAILS WITH 1/2" Ø 28 DIAMETER SHANK @ 7" O.C. HEAD, SPACED 8" O.C.
@ 7" O.C. HEAD, SPACED 8" O.C.
G-P GYPSUM CORP. - TYPE DDDG3 (FINISH RATING 20 MIN.)
4. EAGLE GYPSUM PRODUCTS - TYPE EGX-7 (FINISH RATING 20 MIN.)
5. G-P GYPSUM CORP. - TYPES 5, 9, C, TYPE DGG (FINISH RATING 20 MIN.), TYPE GPF52 (FINISH RATING 24 MIN.), TYPE GPF53 (FINISH RATING 20 MIN.), TYPE GPF56 (FINISH RATING 20 MIN.) TYPE GPF5-C (FINISH RATING 20 MIN.)
6. 1/2" Ø GALV. NAILS - EXPOSED OR COVERED WITH PAPER TAPE & JOINT COMPOUND, FOR TAPERED, ROUNDED-EDGE WALLBOARD, JOINTS COVERED WITH PAPER TAPE & JOINT COMPOUND *BEARING THE UL CLASSIFICATION MARKING



TRUSS NOTES FOR G.C.:

ROOF TRUSSES MUST BE DESIGNED BY AN
ENGINEER OR SUBMITTED TO A TRUSS
MANUFACTURER FOR DESIGN PRIOR
TO CONSTRUCTION. jGroves design co.
IS NOT RESPONSIBLE FOR TRUSS DESIGN OR
LOAD/SPAN CALCULATIONS.

IF FLOOR TRUSSES ARE USED

TRUSS NOTES FOR G.C.:

FLOOR TRUSSES MUST BE DESIGNED BY AN ENGINEER OR SUBMITTED TO A TRUSS MANUFACTURER FOR DESIGN PRIOR TO CONSTRUCTION. jGroves design co. IS NOT RESPONSIBLE FOR TRUSS DESIGN OR LOAD/SPAN CALCULATIONS.

2 HOUR

PARTY WALL DETAIL

SCALE: 1/2" = 1'-0"

EAST 5TH STREET
TOWNHOMES
CROSSVILLE, TN

jGroves design company
Jon J. Groves
P.O. Box 1463
Cookeville, TN 38503
Phone : 931-644-4791
jgrovesdesignco@gmail.com

This drawing and the design shown is the property of jGroves design company. The reproduction, copying or use of this drawing without their written consent is prohibited and any infringement will be subject to legal action

REVISIONS
1.
2.
3.
4.
5.
6.
7.
8.

SIGNATURES:

JOB # 02_25009

DWN. BY: JJG

DATE: 4.9.25

SHEET NAME:


GENERAL NOTES

SHEET:


G-1

SIGNATURES:
JOB # 02_25009
DWN. BY: JJG
DATE: 4.9.25
SHEET NAME:
SITE PLAN
SCALE: AS NOTED


C-1.0




- LEGEND**
- 0.5" Iron Rod (New)
 - ⊕ Sewer Manhole
 - s— Gravity Sewer Line
 - ⊗ Fire Hydrant
 - ⊠ Water Meter
 - w— 8" Water Line (See Note 2)
 - ⊙ Utility Pole
 - E— Overhead Utility Line




2
A-O.1 FOUNDATION DETAIL
SCALE: 3/4" = 1'-0"




3
A-O.1 THICKENED SLAB DETAIL
SCALE: 3/4" = 1'-0"



4
A-O.1 CONTROL JOINT DETAIL
SCALE: 3/4" = 1'-0"



5
A-O.1 TYPICAL CMU CORNER DETAIL
SCALE: 3/4" = 1'-0"



1
A-O.1 FOUNDATION PLAN
SCALE: 1/4" = 1'-0"

CMU WALL REINFORCEMENT TABLE

WALL HT.	VERTICAL REBAR
0'-0"-48"	#4 @ 32" O.C.
48" -60"	#4 @ 24" O.C.
60"-84"	#4 @ 12" O.C.

NOTES:

- 1.) TYPICAL TOP OF FOOTING TO BE A MIN. OF 18" BELOW UNDISTURBED SOIL
- 2.) CORE FILL REINFORCED CMU WALL CELLS
- 3.) REINFORCE WALL CORNERS. #4 VERT. REBAR

NOTES

1. CONTROL JOINTS NOT TO EXCEED AN AREA OF 400 SQ. FT. THE CONTROL JOINT SHALL BE $\frac{1}{4}$ OF THE SLAB THICKNESS AND $\frac{1}{8}$ IN WIDTH.
2. 4" , 3,000 psi CONCRETE SLAB REINFORCED WITH WWF 6X6-W1.4XW1.4 ON 10 MIL (MIN) VAPOR BARRIER ON 4" SPECIFIED AGGREGATED FILL. CONFORM TO THE GEOTECHINCAL ENGINEER REQUIREMENTS FOR SUB-GRADE PREPARATION.
3. G.C. TO VERIFY ALL DIMENSIONS PRIOR TO STARTING CONSTRUCTION
4. CONTINUOUS PERIMETER FOOTINGS OR CONCRETE TURNDOWNS TO BE A MIN. OF 24" WIDE X 12" DEEP WITH (2) #4 REBAR
5. SAFE SUB GRADE BEARING CAPACITY FOR FOOTINGS SHALL BE A MIN. OF 3,000 P.S.F.
6. CONCRETE FOOTINGS SHALL HAVE A MIN. COMPRESSIVE STRENGTH OF 3,000 P.S.I.
7. PROVIDE MASONRY LEDGES FOR BRICK OR STONE VENEER
8. CONTACT THIS OFFICE IF ANY DISCREPANCIES OCCUR.


WALL LEGEND

	8" SPLIT FACED CMU FOUNDATION WALL W/ CONTUOUS REINF. CONCRETE FOOTING
--	--


REVISIONS	1.	2.	3.	4.	5.	6.	7.	8.
SIGNATURES:								
JOB #	02_25009							
DWN. BY:	JJG							
DATE:	4.9.25							
SHEET NAME:	FND PLAN & DETAILS							
SCALE:	AS NOTED							

SHEET:

A-0.1



2
A-1.0
DIMENSIONED
FIRST FLOOR PLAN
SCALE: 1/4" = 1'-0"



1
A-1.0
NOTED
FIRST FLOOR PLAN
SCALE: 1/4" = 1'-0"

PLAN NOTES

1.) TYPICAL CEILING HT. 9'-0"

GENERAL NOTES

- DO NOT SCALE DRAWINGS.
- CLEARANCE DIMENSIONS SHALL BE MAINTAINED ESPECIALLY AT HANDRAILS, GRAB BARS & PLUMBING FIXTURES.
- THE CONTRACTOR SHALL FIELD MEASURE BEFORE STARTING CONSTRUCTION & SHOP DRAWINGS.
- NOTIFY THE DESIGNER OF ANY VARIATION REQUIRED IN THE DIMENSIONS, WHETHER NOTED FOR VERIFICATION, FOR THE INSTALLATION OF EQUIPMENT OR OTHERWISE BEFORE CONTINUING WITH THE WORK.
- IN THE EVENT CLARIFICATION IS NEEDED, NOTIFY THE DESIGNER BEFORE CONTINUING WITH THE WORK IN QUESTION.
- PROVIDE SOUND INSULATION AND
- DOOR JAMBS TO HAVE A MIN. OF 4" RETURN
- LUMBER SUPPLIER TO VERIFY ALL BEAM AND FLOOR JOIST SIZES, SPANS, SPACING, AND CONNECTORS.
- THE CONTRACTOR IS SOLELY RESPONSIBLE FOR DIMENSIONS ON THE SHOP DRAWINGS.

WALL LEGEND

- EXTERIOR WALL - 3-1/2" WOOD STUDS AT 16" C. WITH MIN. 13 INSULATION, AND 1/2" EXTERIOR SHEATHING, VAPOR BARRIER, & HARDIE PLANK SIDING
- INTERIOR WALL - 3-1/2" STUDS AT 16" O.C. WITH 1/2" GYP. BD. EACH SIDE
- INTERIOR PLUMBING WALL - 5-1/2" STUDS AT 16" O.C. WITH 1/2" GYP. BD. EACH SIDE
- 2 HOUR PARTY WALL-REFER TO DETAIL 1-G-1

REVISIONS	1.	2.	3.	4.	5.	6.	7.	8.
SIGNATURES:								
JOB #	02_25009							
DWN. BY:	JJG							
DATE:	4.9.25							
SHEET NAME:	FIRST FLOOR PLANS							
SCALE:	AS NOTED							
SHEET:								

DOOR SCHEDULE


PER FIRST FLOOR					
SYM	WIDTH	HEIGHT	DESCRIPTION	LOCATION	QTY
1	3'-0"	6'-8"	TOWNHOUSE ENTRY	EXTERIOR	3
2	3'-0"	6'-8"	LAUNDRY	INTERIOR	3
3	2'-8"	6'-8"	BEDROOM	INTERIOR	3
4	2'-6"	6'-8"	CLOSET	INTERIOR	3
5	2'-6"	6'-8"	MECH	INTERIOR	3
6	2'-6"	6'-8"	BATH	INTERIOR	3

DOOR SCHEDULE

PER SECOND FLOOR					
SYM	WIDTH	HEIGHT	DESCRIPTION	LOCATION	QTY
7	2'-6"	6'-8"	BATHROOM	INTERIOR	3
8	2'-6"	6'-8"	CLOSET	INTERIOR	3
9	2'-8"	6'-8"	BEDROOM	INTERIOR	3
10	2'-6"	6'-8"	BATHROOM	INTERIOR	3
11	2'-6"	6'-8"	CLOSET	INTERIOR	3
12	2'-8"	6'-8"	BEDROOM	INTERIOR	3
13	2'-6"	6'-8"	CLOSET	INTERIOR	3
14	2'-6"	6'-8"	BATH	INTERIOR	3

OVERALL WINDOW SCHEDULE

*ALL WINDOWS TO HAVE DOUBLE INSULATED GLASS




*ALL WINDOWS TO HAVE DOUBLE INSULATED GLASS

OVERALL		
WINDOW SCHEDULE		
SIZE	SYM	QTY
3'X5'	A	12
2'X3'	B	3

WINDOW & DOOR NOTE

FINAL WINDOW AND DOOR SELECTION, STYLE, MATERIAL, BRAND, & COLOR TO BE SELECTED BY OWNER AND COORDINATED WITH GENERAL CONTRACTOR.



TYPICAL WOOD DOOR JAMB

SCALE: 3" = 1'-0"

REVISIONS
1.
2.
3.
4.
5.
6.
7.
8.

SIGNATURES:

JOB # 02_25009

DWN. BY: JJG

DATE: 4.9.25

SHEET NAME:


DOOR & WINDOW SCH

SCALE: AS NOTED

SCALE: AS NOTED

SHEET.

A-2.0



IF ROOF TRUSSES ARE USED

TRUSS NOTES FOR G.C.:

ROOF TRUSSES MUST BE DESIGNED BY AN
ENGINEER OR SUBMITTED TO A TRUSS
MANUFACTURER FOR DESIGN PRIOR
TO CONSTRUCTION. jGroves design co.
IS NOT RESPONSIBLE FOR TRUSS DESIGN OR
LOAD/SPAN CALCULATIONS.

NOTES:

- 1.) PROVIDE 6" GUTTERS AND DOWN SPOUTS AS NECESSARY
- 2.) PROVIDE PROPER ROOF VENTILATION (RIDGE + SOFFIT VENTS)
- 3.) TYPICAL FINISHED OVERHANGS TO BE 1'-0"

EAST 5TH STREET
TOWNHOMES
CROSSVILLE, TN

jGroves design company
Jon J. Groves
P.O. Box 1463
Cookeville, TN 38503
Phone : 931-644-4791
jgrovesdesignco@gmail.com

This drawing and the design
shown is the property of
jGroves design company. The
reproduction, copying or use
of this drawing without their
written consent is prohibited
and any infringement will be
subject to legal action

REVISIONS	1.	2.	3.	4.	5.	6.	7.	8.
SIGNATURES:								
JOB #	02_25009							
DWN. BY:	JJG							
DATE:	4.9.25							
SHEET NAME:	ROOF PLAN							
SCALE:	AS NOTED							
SHEET:	A-3.0							


jGroves
design company

REVISIONS	1.	2.	3.	4.	5.	6.	7.	8.

SIGNATURES:
JOB # 02_25009
DWN. BY: JJG
DATE: 4.9.25
SHEET NAME:
EXTERIOR ELEVATIONS
SCALE: AS NOTED


SHEET:

A-4.0




2 SIDE ELEVATION
A-4.0 SCALE: 1/4" = 1'-0"

1 FRONT ELEVATION
A-4.0 SCALE: 1/4" = 1'-0"



3 SIDE ELEVATION
A-4.0 SCALE: 1/4" = 1'-0"

4 REAR ELEVATION
A-4.0 SCALE: 1/4" = 1'-0"



REVISIONS
1.
2.
3.
4.
5.
6.
7.
8.